

2022 WIRE CLASS COMPACTS

For questions, please call/TEXT one of the following:

BOB HEAD@ 716-487-7510

DEREK HEAD@ 716-487-6428

SPENCER SHIRLEY@ 716-352-4432

ALL CARS MUST BE COMPLETELY STOCK UNLESS OTHERWISE NOTED.

FUEL AND BATTERIES

- Factory gas tanks may be left under car if in front of rear wheels.
- If running factory tank, you must have (2) other forms of safety on it such as 9 wire, chains or ratchet straps.
- Batteries may be moved inside the car on the passenger side floor.
- Factory fuel tanks may NOT be used inside the car!!
- Any leaking fuel cell will be turned away and won't pass inspection until the leak is sealed.

BODY/CAGE

- Hood must have a 12x12 hole for fire safety.
- Hood may be chained or wired in up to (6) spots of your choice and may also be chain or wired around the bumper in (2) of those (6) spots.
- Trunk must be chained or wired in up to (6) spots of your choice.
- There is to be no flat decking or wedging. Creasing may be done at a minimum.
- Doors may be chained or wired in up to (6) spots of your choice PER door.
- Drivers' door may be welded solid and may also have another form of protection.
- You may run a 4-point cage with a halo bar.
- Cage material may be no larger than 4x4 or 2x6 1/4" channel.
- Cage material must be no thinner than 1/8 inch and absolutely no perforated tubing.
- Cage material must be 6 inches off the floor.
- Sides (door bars) must be no longer than 6 inches past the seat bar.
- Gas Tank protectors are permitted and must be no larger than 24Lx24Wx20H
- Tank protectors must be at least 2 inches off the floor and 2 inches away from the speaker deck. (pre ran cars will have exceptions)
- You must have at least (1) windshield bar at least 1" wide running from the cowl area to the roof unless you keep windshield in place.
- Back window bars are NOT permitted.

BUMPERS

- Bumpers must remain stock. FACTORY PLASTIC BUMPER COVERS MUST BE REMOVED BEFORE ENTERING VENUE.

- Bumpers swaps are permitted but must be from another compact style car FROM SAME TIME PERIOD.
- Bumpers may be welded on WITH NO EXTRA METAL

TIRES AND WHEELS

- STOCK DOT TIRES ONLY. MUST HAVE A DOT STAMP.
- Tires may be doubled or tubed.
- Stock wheels must be used.
- Side wall protectors, valve stem protectors, bead locks are NOT permitted.
- All wheel weights MUST be removed. This is for the safety of fellow drivers, fans and officials.

SUSPENSION

- All suspension components must be stock.
- No solid suspension or aftermarket parts.