

2023 WIRE CLASS COMPACTS

Open to any factory 4- or 6-cylinder compact car.

FOR QUESTIONS, PLEASE CONTACT PERRY SWAB @ MAKIN' JUNK PRODUCTIONS

FUEL AND BATTERIES

- Factory gas tanks may be left under car if in front of rear wheels.
 - If running factory tank, you must have (2) other forms of safety on it such as 9 wire, chains, or ratchet straps. (MUST WRAP AROUND FLOORBOARD)
 - **NO FACTORY TANKS MAY BE PLACED INSIDE OF THE CAR.**
 - Any leaking fuel cell will be turned away and won't pass inspection until the leak is sealed.
- Batteries may be moved inside the car on the passenger side floor and must be securely fastened.

BODY/CAGE

- Hood must have a 12x12 hole for fire safety.
- **HOODS may be fastened shut in 1 of 2 ways.**
 - **You may weld angle iron no longer than 3 inches to you fender/hood.**
 - **You may wire or chain your hood in up to 6 spots. 2 of the 6 may go to your bumper.**
- Trunk must be chained or wired in up to (6) spots of your choice.
 - There is to be no flat decking or wedging. Creasing may be done at a minimum.
- Doors may be chained or wired in up to (6) spots of your choice PER door

- Drivers' door may be welded solid and may also have another form of protection.
- You may run a 4-point cage with a halo bar.
 - (2) gussets allowed inside of cage.
 - 4x4 or 2x6 max material size
 - Cage material must be no thinner than 1/8 inch and no perforated tubing.
 - Cage material must be 6 inches off the floor.
 - Sides (door bars) must be no longer than 6 inches past the seat bar.
- Gas Tank protectors are permitted and must be no larger than 24Lx24Wx20H
 - Tank protectors must be at least 2 inches off the floor and 2 inches away from the speaker deck. (pre ran cars will have exceptions if floor is buckled)
- You must have at least (1) windshield bar at least 1" wide running from the cowl area to the roof unless you keep windshield in place.
- Back window bars are NOT permitted.
- **FIX IT PLATES- No fix it plates on fresh cars. Only fix it plates allowed must be placed on repaired areas approved by promoter/inspectors. 4x4 plate size.**
 - **Any pre ran car with damage to the frame is only allowed a max of 2 fix it plates per car. 2 PLATES MAX. Must have proof of visible damage.**
- **No wire is permitted anywhere on car unless otherwise stated.**
- Fresh cars may use (2) strands of 9 wire in 2 locations of choice behind rear seat bar.

- o Preran cars may use 4 locations. Nothing up front unless otherwise stated.

BUMPERS

- Bumpers must remain stock. FACTORY PLASIC BUMPER COVERS MUST BE REMOVED BEFORE ENTERING VENUE.
 - o Bumpers swaps are permitted but must be from another compact style car FROM SAME TIME PERIOD.
 - o Bumpers may be welded on WITH NO EXTRA METAL
 - o You may have wire from your core support to you bumper in 2 locations. We do not want bumpers falling off.

TIRES AND WHEELS

- STOCK DOT TIRES ONLY. MUST HAVE A DOT STAMP.
- Tires may be doubled or tubed.
- Stock wheels must be used.
- Side wall protectors, valve stem protectors, bead locks and bead protectors are NOT permitted.
- All wheel weights MUST be removed. This is for the safety of fellow drivers, fans, and officials.
- **Solid rear tires are permitted.**

SUSPENSION/DRIVETRAIN

- All suspension components must be stock.
- No solid suspension
- No solid motor mounts