

2024

BUMPER SWAP COMPACT

GENERAL RULES:

1. Must be registered before inspection.
 2. Anything deemed excessive will be at official's discretion.
 3. If the rules do not say you can do it, don't.
-
1. **Front wheel drive 4/6 cylinder only.**
 2. **Cars must remain stock unless otherwise specified.**
 3. **Simplified harness allowed.**
 4. **No aftermarket oil coolers or tranny coolers.**
 - a. Factory tranny lines may be looped.
 5. **Factory or looped water systems only.**
 - a. No water boxes.
 - b. No rad guards
 - c. No expanded metal.
 6. **All doors may be wired or chained 8 spots per door max.**
 - a. 1-inch holed washer method permitted.
 - b. Drivers' door may be welded solid.
 7. **Deck lids may be wired or chained in 8 spots max.**
 - a. 1-inch holed washer method permitted.
 - b. Wiring can go to floor in spare tire area but cannot wrap around frame.
 8. **Hood may be wired in 6 spots max.**
 - a. You may use 1-inch holed washer method.
 - b. Must have a 12x12 fire hole.
 - c. Must be open for inspection.
 9. **Creasing of rear quarter panels permitted but must remain factory height.**
 - a. May tuck and dish trunk.

10. Frames may be hardnosed, but the core support may not be moved/removed.

- a. No extra body mounts.
- b. No fix it plates on fresh cars.
- c. No seam welding
- d. Pre ran cars with damage must get approval first for fix it plates.

11. Any factory car bumper may be used.

- a. Bumpers may be seam welded but not loaded.
- b. 4x4x1/4 tubing may be used.
 - i. If using this, you must keep ends open.
 - ii. No loading and no homemade point.
- c. SMW LIGHT or MARK DOWD permitted.
 - i. 1/4 inch or less
 - ii. No gussets
 - iii. Ends must be open.

12. You may have a 6"x8" plate flat to front of frame for mounting purposes.

- a. (1) 4"x 4" 1/4" plate per rail may be used to help attach bumper.
- b. Must be welded to bumper and to the unibody only.
- c. 2 strands of wire in 2 locations may go from core support to bumper.

13. Windshield must have wire or strapping.

14. Rear window bars are not permitted.

15. Battery may be moved to inside of car but does not have to be.

- a. Must be securely fastened.

16. If gas tank is moved from under the car you must use a fuel cell, not a factory gas tank.

17. Any air filled front tires.

- a. May be doubled/tubed.
- b. no bead locks or Lip protectors are permitted.
- c. Rear tires may be solid.

18. 4-point cages recommended

- a. May have center bar for shifter only.
- b. Door bars may not exceed 6 inches past B-pillar.
- c. All cage material must remain 6 inches from the floor.
- d. No kickers/down legs.
- e. Halo bars permitted and must be straight up and down.
 - i. May connect windshield bar to halo.

19. Tank protectors permitted.

- a. May be no larger than 32 inches wide x 24 inches long x 24 inches tall.
- b. Must remain 4 inches from package tray and must be mounted to back bar.

i. This will be strictly enforced.

20. Aftermarket shifters are permitted.

21. Headers are permitted.

22. Spring risers are permitted.

- a. No solid suspension.
- b. All suspension components must remain stock.

23. NO extra plates, NO extra wire.